

Tomorrow's Technology Today



Low Voltage Electronic Specialist

TIPS FOR VIEWING THIS PRESENTATION:

1. Take advantage of the built-in **Table of Contents** by clicking on the **palette icon** (show/hide navigation pane) located just to the right of the printer icon. Or you can go up to **WINDOW...** then select **Show Bookmarks**.
2. After selecting from the menu on the left, click on the palette icon once more and the selected section will open full screen for easy viewing.
3. To go to a website on the Internet from this pdf file, right click on the web or email address, then select **"Open Weblink in Browser"**.



Electronic Communicating Thermostat

- Single stage heating and cooling systems, non heat pump
- 1 stage heat, 1 stage cool
- Can be set to heat only or cool only
- Adjustable anticipator
- Can power steal for retrofitting heat/cool systems with only 4 wires
- Use for forced air, radiant heat, hydronic heat, steam, electric, gas, oil, etc.
- Auto changeover (will switch from heat to cool automatically)
- Programmable (if used stand alone, thermostat can be programmed for weekdays, Saturday and Sunday - 4 times per day)
- High and Low setting limits
- Outdoor temperature display (when connected to Omni, OmniPro or other system)
- Time display - time is displayed and is set automatically when connected to Omni, OmniPro or other system
- Filter reminder - tracks time that fan has run, indicates "FILT" to suggest changing filter
- Day/Night mode (a simple way to set preprogrammed day and night temperatures by remote control)
- No batteries - all memory is non-volatile
- Are UL and EPA approved and Energy Star listed
- Celsius or Fahrenheit, 24 hour or AM/PM time format
- Dimensions: 5.5" W x 3.75" H x 1.1" D

Contact Us @



www.aicorp.net

sales@aicorp.net

(808) 722-8677